

**Premium stackable
10/100 switches deliver
maximum security,
convergence features
and intelligence
required by the most
demanding advanced
enterprise networks**

OVERVIEW

The 3Com® Switch 5500 10/100 Family delivers premium levels of performance, security and reliability for robust switching at the enterprise network edge. The family consists of Layer 2/3/4 Fast Ethernet and Power over Ethernet switches, with advanced features that can accommodate the most demanding applications, offering resilient and secure connectivity and the latest traffic-prioritization technologies to optimize applications on converged networks. Designed for maximum flexibility and scalability, 3Com Switch 5500 models come with 24 or 48 10/100 ports, plus four active SFP-based Gigabit Ethernet ports for stacking and uplinks.

The switches can be stacked up to eight units high in one location, or they can be distributed over several sites up to 70 km (43.5 miles) apart and connected via Gigabit links to form a virtual “stack.” One stack can provide up to 384 Fast Ethernet ports and may be managed centrally as a single-IP entity. Each stack offers chassis-like availability and resiliency over traditional aggregated-trunk configurations with patented 3Com XRN® (eXpandable Resilient Networking) stacking technology.

Further expansion is possible via clustered stacking technology, allowing single IP management for up to 32 devices from different 3Com switch families, including the Switch 5500G-EI, 5500-EI, 4500G and 4200G.

KEY BENEFITS

ENTERPRISE-LEVEL PERFORMANCE

3Com Switch 5500 10/100 devices provide switching capacity of up to 17.6 Gbps for 52-port models and 12.8 Gbps for 28-port models. Wirespeed and line-rate performance is delivered on all ports within the stack. Advanced Layer 3 routing—including OSPF, PIM-SM, PIM-DM and RIP v1/v2—helps deliver optimal performance and system response.

These switches have Enhanced-Image (EI) software, which offers Enterprise-class switching features including more MAC addresses, static routes and IP interfaces, greater number of virtual LANs (VLANs), extended port mirroring, Layer 3 OSPF and multicast routing, enhanced resiliency via 3Com XRN stacking technology and IEEE 802.3af Power over Ethernet (PoE) support.



from top: 3Com Switch 5500-EI 28-Port FX, Switch 5500-EI 52-Port, Switch 5500-EI 28-Port, Switch 5500-EI PWR 52-Port, Switch 5500-EI PWR 28-Port

KEY BENEFITS (CONTINUED)

HIGH AVAILABILITY FOR CRITICAL APPLICATIONS

XRN technology, a 3Com innovation, enables multiple interconnected and stackable Layer 3 switches to be managed as a single entity. Stack and switching fabric setup is automated and provides a high level of resiliency and continuous availability without adding to network complexity. After configuration, all switches actively share routing intelligence and network loads—eliminating the wasted bandwidth and added expense of a passive standby unit. Ultra-fast failover recovery automatically redistributes traffic among the other active units in case a switch becomes disconnected or fails.

MULTILAYER SECURITY

The Switch 5500 family provides integrated and distributed security enforcement that can be managed from a central location. Access control lists (ACLs) help protect network resources from unauthorized access and data corruption. User-based authentication and DES 56/168-bit[†] encryption help secure Layer 3 protocols and management controls such as SSH v2 and SNMP. IEEE 802.1X RADIUS/TACACS+ network login and RADIUS Authenticated Device Access (RADA) enforce access control at the network edge.

FLEXIBLE, SECURE FIBER CONNECTIONS

The Switch 5500-EI FX is ideally suited for applications where security is of paramount importance, or where long cable runs are required. This switch provides connections on fiber infrastructures that are almost impervious to electronic eavesdropping because they use optical transmission. The switch uses 100BASE-X SFP transceivers for its 24 100 MB connections, providing the flexibility of running any mix of 100BASE-FX multimode fiber (up to 2 km/1.2 miles) or 100BASE-LX10 single-mode fiber (up to 10 km/6.2 miles). The Switch 5500-EI FX supports all the advanced EI features.

PRIORITY FOR CONVERGED BUSINESS TRAFFIC

Next-generation traffic prioritization features—including advanced policy-based Class of Service/Quality of Service (CoS/QoS), eight priority queues, committed access rates, bandwidth limiting and filtering and more—identify and optimize delay-sensitive traffic such as voice and video. To help assure this optimization, switches can be configured to automatically isolate voice traffic from 3Com and other IP telephony systems within a voice-dedicated VLAN.

UNIQUE AC/DC POWERED OPERATION

3Com Switch 5500 products are the first stackable switches to support multiple power schemes right out of the box, with a choice of AC, AC and DC, or DC operation. Select EI models also support IEEE 802.3af PoE, enabling power to be injected out to the edge of the network without the need to install additional wires or upgrade existing power supplies. An available Redundant Power System can provide supplemental N+1 power across all PoE ports in the system.

[†] 168-bit encryption not available in all countries. Refer to www.3com.com for details.

KEY BENEFITS (CONTINUED)

POWERFUL, UNIFIED MANAGEMENT

The 3Com Operating System employed in the Switch 5500 is the same powerful software used in other 3Com enterprise stackable switches as well as in the 3Com Switch 8800 and Switch 7700 modular switch families and the Router 6000, 5000 and 3000 families. This makes for an easy mix-and-match of networking technologies with consolidated administration over the entire network, as well as edge-to-core visibility and control when using 3Com management applications such as 3Com Enterprise Management Suite and 3Com Network Director.

FUTURE-PROOF INVESTMENT

Standards-based switching and management features provide a networking solution that maximizes IT investment and supports emerging standards. Comprehensive IPv6 management features, as well as IPv6 traffic filtering and classification, prepares your network for this next generation IPv6 version while maintaining full compatibility with today's more common IPv4.

WORLD-CLASS SERVICE, SUPPORT AND TRAINING

The 3Com Switch 5500 is backed by 3Com and its authorized partners. Professional customer service organizations offer assessment, installation, management and maintenance support for network infrastructures. Skilled personnel with experience in a variety of network environments can assist 3Com customers through all phases of network planning, implementation, troubleshooting and product training.

FEATURE HIGHLIGHTS

Provides up to 48 10/100 Layer 2/3/4 switched ports per switch and up to 384 10/100 ports per stack

Equipped with four additional Gigabit Ethernet ports for stacking or uplinks

Can be stacked eight units high, or implemented as a distributed stack at multiple locations and managed as a single-IP entity

Delivers wirespeed and line-rate performance on all ports

Offers OSPF and multicast routing, 3Com XRN stacking technology and IEEE 802.3af Power over Ethernet

Provides high resiliency and continuous availability with active load sharing and support for ultra-fast failover recovery

Implements multilayer distributed security including ACLs, DES 56/168-bit[†] encryption, IEEE 802.1X network login and RADA authentication

Prioritizes converged network traffic with advanced CoS/QoS and other features to ensure high levels of service for latency-sensitive applications

Leverages existing power schemes in data centers and switching infrastructures with built-in support for both AC and DC power


Consolidates administrative control and enhances core-to-edge visibility with an operating system shared with 3Com modular switches and routers

Offers a fiber model for increased security and infrastructure flexibility

Backed by top-flight service, support and training from 3Com and 3Com authorized partners

[†] 168-bit encryption not available in all countries. Refer to www.3com.com for details.

3COM SWITCH 5500 FAMILY IN AN ENTERPRISE CAMPUS NETWORK



PRODUCT WARRANTY AND OTHER SERVICES

Warranty	3Com Limited Lifetime Warranty. For as long as the original end user owns the product, or for five years after 3Com discontinues the sale of the product, whichever occurs first.
Hardware coverage	Covers the complete unit including power supply and fan.
In-warranty hardware replacement [†]	Advanced Hardware Replacement of hardware for the duration of the warranty. In the US 48 contiguous states this is same-day ship with next business day delivery when call received before noon Pacific time. For Canada, Alaska and Hawaii, this is same-day ship when call received before noon Pacific time. For the rest of the world, it is next-business-day ship. Actual delivery times may vary depending on customer location. Reasonable commercial efforts apply.
Software coverage	90 days for media replacement.
Software updates*	Access to releases with incremental software features and bug fixes. For the Switch 5500, updates are all releases within the licensed 3Com OS software level.
Online Knowledgebase support*	Access to online troubleshooting tool for the duration of the warranty.

* These services are not included as part of the Warranty and 3Com reserves the right to modify or cancel this offering at any time, without advance notice. This offering is not available where prohibited by law. Services are effective at warranty start date, and are enabled with product registration. Customers receive a user ID with eSupport registration.

SERVICE AND SUPPORT

3Com Global Services offers the resources and talents of a major corporation plus more than two decades of experience in resolving network challenges and delivering business benefits to enterprises around the world.

Global support with a personalized focus in the local language helps drive productivity and minimize expenses. Because 3Com understands both the technology and the business, we're the partner you need, to maintain your competitive edge and remain strong.

Suggested Service, Support and Training Offerings

Network Health Check	<p>An activity-auditing service focused on improving network performance and productivity</p> <p>Includes traffic monitoring, utilization analysis, problem identification, and asset deployment recommendations</p> <p>Extensive report provides blueprint for action</p>
Network Installation and Implementation Services	<p>Experts set-up and configure equipment and integrate technologies to maximize functionality and minimize business disruption</p> <p>For large and complex sites, implementation services include personalized configuration, project management, extended testing and coaching on network administration</p>
Project Management	<p>Provides extra focus and resources that special projects demand</p> <p>3Com engineers manage entire process from initial specifications to post-project review</p> <p>Using structured methodology, requirements are identified, projects planned and progress of implementation activities tracked</p>
3Com Guardian SM Maintenance Service	This service provides comprehensive on-site support and includes advance hardware replacement, telephone technical support and software upgrades
3Com Express SM Maintenance Service	This service provides speedy access to: 3Com shipment of advance hardware replacements, software upgrades and telephone support
3Com University	Self-paced and instructor-led technology and product courses, plus certification programs

SPECIFICATIONS

All information in this section is relevant to all members of the 3Com Switch 5500 10/100 family, unless otherwise stated.

CONNECTORS

52-port models

48 auto-negotiating 10BASE-T/100BASE-TX ports configured as auto-MDI/MDIX; IEEE 802.3af in-line power for PWR models

4 Gigabit SFP ports

28-port non-FX models

24 auto-negotiating 10BASE-T/100BASE-TX ports configured as auto-MDI/MDIX; IEEE 802.3af in-line power for PWR models

4 Gigabit SFP ports

28-port FX

24 SFP ports, to be populated with 100BASE-X SFP multi- or single-mode transceivers

2 auto-negotiating 10BASE-T/100BASE-TX/1000BASE-T ports configured as auto-MDI/MDIX

2 Gigabit SFP ports

PERFORMANCE

52-port

17.6 Gbps switching capacity, max.

13.1 Mpps forwarding rate, max.

28-port

12.8 Gbps switching capacity, max.

9.5 Mpps forwarding rate, max.

All models

Switch fabric bandwidth: 32 Gbps

Wirespeed performance across all ports within stack or fabric

Store-and-forward switching;

latency <10 µs

2 Gbps full-duplex stacking bandwidth

LAYER 2 SWITCHING

16K MAC addresses in address table

256 Static MAC addresses, in addition to default address

Jumbo Frame support

4,094 port-based IEEE 802.1Q VLANs

IEEE 802.1 Q-in-Q double-tagged VLANs

IEEE 802.1v protocol-based VLANs

MAC-based VLANs using RADA auto-VLAN assignment

Auto-voice VLAN

IEEE 802.3ad Link Aggregation Control Protocol (LACP); automated and manual aggregation

Link aggregation trunk groups, per switch:

- 26 (52-port); 14 (28-port)
- 8 10/100 ports or 8 SFP ports per group
- 8 Distributed Link Aggregation (DLA) groups

Auto-negotiation and manual configuration of port speed and duplex

IEEE 802.3x full-duplex flow control

Back pressure flow control for half-duplex

Unidirectional Link Detection (UDLD)

Broadcast, Multicast and Unicast traffic suppression

Wake-on-LAN support

IEEE 802.1D Spanning Tree Protocol (STP)

IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

Bridge Protocol Data Unit (BPDU) protection

Spanning Tree root guard

Internet Group Management Protocol (IGMP) v1, 2 and 3 snooping

IGMP querier

Filtering for 256 multicast groups

Dynamic Host Configuration Protocol Relay (DHCP) Option 82

LAYER 3 SWITCHING

Hardware based routing

256 static routes, in addition to default address

Address Resolution Protocol (ARP) entries: 4K dynamic, 1K static

32 IP interfaces

Routing Information Protocol (RIP), v1 and v2: 2K routes

Open Shortest Path First (OSPF):

- 2 areas with 4 virtual interfaces per area
- 2 neighbors per virtual interface
- 2 virtual links

Protocol Independent Multicast-Dense Mode (PIM-DM)

Protocol Independent Multicast-Sparse Mode (PIM-SM)

IGMP v1 and v2

Equal Cost Multipath Protocol (ECMP)

Multicast VLAN Registration (MVR)

DHCP Relay: 4 K max.

3Com XRN® Technology:

- Resilient stacking and fabric links up to 70 km (43.5 mi)
- Distributed Link Aggregation, hot-swappable switch units; high-speed fully resilient trunks up to 8 Gbps
- Distributed Resilient Routing: optimized Layer 3, one routing table per switch

Virtual Router Redundancy Protocol (VRRP)

CONVERGENCE

8 hardware queues per port

IEEE 802.1p Class of Service/Quality of Service (CoS/QoS) on ingress and egress

Remarking of packets based on priority:

- Type of Service (ToS)
- IEEE 802.1p CoS
- IP precedence
- Physical port
- Source/destination MAC address
- VLAN information
- Ethertype
- Source/destination IP address
- Source/destination TCP port
- Source/destination UDP port

Traffic redirection

Time-based Access Control Lists (ACLs)

Auto-prioritization of voice traffic determined by vendor OUI

Weighted Round Robin (WRR), including WRR+SP

Strict Priority Queuing (SPQ)

Weighted Random Early Discard (WRED)

DiffServ Code Point Expedited Forwarding (DSCP EF) remarking for prioritization of VoIP traffic

Application rate limiting and blocking on ingress

Port-based traffic shaping on egress

IEEE 802.3af Power over Ethernet standards-compliant (PWR models)

POE (PWR MODELS ONLY)

IEEE 802.3af PoE injection into Cat5 or 5e LAN wiring (300 W total max.)

Supports all standard and most common pre-standard phones, access points and other PoE devices from selected vendors (Cisco, Nortel, Philips, Siemens, Avaya, NEC, Polycom, Pingtel, Proxim, et. al.)

Available standards-based supplemental power system enables full 15.4 W to all PoE ports in a switch or stack

SECURITY

IEEE 802.1X Network login user authentication:

- Local, RADIUS, or TACACS+ server authentication
- PAP, CHAP, EAP over LAN (EAPoL), EAP-TLS/TTLS and PEAP
- Automatic port assignment of VLANs, ACLs and QoS profile based on user
- Multiple users per port
- 1,024 users per fabric
- Guest VLAN option
- Multiple authentication server realm definitions

RADIUS/TACACS+ session accounting

RADIUS Authenticated Device Access (RADA): authenticate devices based on MAC address against RADIUS server or local database; assign VLAN ID and ACL through RADIUS

Combined MAC and IEEE 802.1X authentication on same port

DHCP Tracker

DHCP snooping, including DHCP Trust

Wirespeed packet filtering in hardware

ACLs filter at Layers 2, 3 and 4:

- Source/destination MAC address
- Ethernet type
- Source/destination IP address
- Source/destination TCP port
- Source/destination UDP port

User-defined ACL filters

VLAN-based ACLs

Port-based MAC address Disconnect Unknown Device (DUD)

ARP inspection and IP source guard

Proxy ARP

IEEE 802.1X or TACACS+ user authentication of switch management on Telnet and console sessions

MD5 cipher-text and clear-text authentication for OSPF v2 and RIP v2 packets and SNMP v3 traffic

Hierarchical management and password protection for management interface and encrypted traffic, with SNMP v3 and SSH v2

4 local user access privilege levels

Trusted management station IP and/or MAC address

STACKING

Up to 400 user ports, including up to 384 10/100 ports

Single IP address and management interfaces for stack-wide control

Hot-swappable, resilient stacking

Distributed stacking over standard media with links up to 70 km (43.5 mi)

Distributed Resilient Routing with router tables in all units; no master/slave arrangement

Combine any Switch 5500-EI models into a single stack, up to 8-high, when using XRN technology

Clustered stacking technology: single IP management for up to 32 devices from different 3Com switch families, including Switch 5500G-EI, 5500-EI, 4500G and 4200G

Clustered stacking technology: single IP management for up to 32 devices from different 3Com switch families, including Switch 5500G-EI, 5500-EI, 4500G and 4200G

MANAGEMENT

CLI via console or Telnet

Embedded web management interface

System configuration with SNMP v1, 2c and 3

Comprehensive statistics, including ACL/QoS and IP interface

Syslog

IPv6 management including pingv6, tracertv6, Telnetv6, TFTPv6, DNSv6 and ARPv6

IPv6 management interface IP address configuration

Remote Monitoring (RMON) groups statistics, history, alarm and events

DHCP server including options 60, 82 and 184

Supports multiple software images and bank swap, stored in non-volatile memory

Configuration conversion tool for migration from Switch 3300, 4200 and 4400 to Switch 5500

1-to-1 port mirroring

Ability to apply ACL to mirror port and forward only certain traffic types

Many-to-1 port mirroring

VLAN-to-1 port mirroring

Remote port mirroring

Detailed alarm and debug information

Front panel indicators for port and unit status information

Supports ping, remote ping and traceroute

Configuration file for backup and restore, stored in non-volatile memory; multiple configuration files available

Backup and restore of software images

Network Time Protocol (NTP)

DHCP Relay and UDP Helper

System file transfer mechanisms: Xmodem, FTP, Trivial FTP (TFTP), Secure FTP (SFTP)

SPECIFICATIONS

(CONTINUED)

3Com management applications:

- 3Com Enterprise Management Suite for flexible, extensible management in advanced enterprise IT environments
- 3Com Network Director for comprehensive, turn-key network management for the enterprise
- 3Com Network Supervisor for basic, turn-key network management for mid-market businesses
- 3Com Network Access Manager for IEEE 802.1X and RADA integration with IAS/Active Directory
- 3Com Switch Manager for virtual clustering support across 3Com switch families

DIMENSIONS

Height: 43.6 mm (1.7 in or 1 RU)

Width: 440.0 mm (17.3 in)

Depth: 270.0 mm (10.6 in)

(PWR models: 427.0 mm (16.8 in))

Weight: 3.3 kg (7.3 lb)

(PWR models: 6.3 kg (13.9 lb))

POWER SUPPLY

Mode support: AC-only, AC and DC, DC-only operation

Built-in DC power stage for direct connection to -48 V supply

AC line frequency: 50/60 Hz

Input voltage: 90-240 VAC

AC current rating: 1.0A max.

(PWR models: 7.0A max.)

DC current rating: 2.0A max.

(PWR 28-port: 12.0A;

PWR 52-port: 19.5A; max.)

Power consumption (max)

28-port non-PWR: 40 W

52-port non-PWR: 50 W

28-port PWR: 70 W, plus up to 300 W for PoE

52-port PWR: 80 W, plus up to 300 W for PoE

28-port FX: 65 W

ENVIRONMENTAL

Operating temperature: 0° to 40°C (32° to 104°F)

Operating altitude: 0 to 4,572 meters (0 to 15,000 feet)

Storage temperature: -40° to 70°C (-40° to 158°F)

Humidity (operating and storage): 10% to 95% non-condensing

Standard: EN 60068 (IEC 68)

Sound pressure level (dBA):

- 52-port: 46.5 decibels
- 52-port PWR: 46.3 decibels
- 28-port: 40.1 decibels
- 28-port PWR: 47.3 decibels
- 28-port FX: 51.3 decibels

Heat dissipation (max)

28-port non-PWR: 140 BTU/hour

52-port non-PWR: 175 BTU/hour

28-port PWR: 245 BTU/hour; excludes heat from PoE

52-port PWR: 275 BTU/hour; excludes heat from PoE

28-port FX: 225 BTU/hour

RELIABILITY

(MTBF @ 25°C)

52-port: 44 years (385,000 hours)

52-port PWR: 21 years (184,000 hours)

28-port: 53 years (464,000 hours)

28-port PWR: 30 years (263,000 hours)

28-port FX: 38 years (332,000 hours)

INDUSTRY STANDARDS SUPPORTED

Ethernet Protocols

IEEE 802.1D (STP)

IEEE 802.1p (CoS)

IEEE 802.1Q (VLANs)

IEEE 802.1s (MSTP)

IEEE 802.1v (Protocol VLANs)

IEEE 802.1w (RSTP)

IEEE 802.1X (Security)

IEEE 802.3 (Ethernet)

IEEE 802.3ab (100BASE-T)

IEEE 802.3ad (Link Aggregation)

IEEE 802.3af (Power over Ethernet)

IEEE 802.3ah (Ethernet in First Mile over Point to Point Fiber - EFMF)

IEEE 802.3i (10BASE-T)

IEEE 802.3u (100BASE-TX/-FX)

IEEE 802.3x (Flow Control)

IEEE 802.3z (100BASE-X)

Management, including MIBs Supported

RFC 768 (UDP)

RFC 783 (TFTP)

RFC 791 (IP)

RFC 792 (ICMP)

RFC 793 (TCP)

RFC 826 (ARP)

RFC 1058 (Routing Information Protocol)

RFC 1112 (IP Multicasting)

RFC 1157 (SNMP)

RFC 1213 (MIB II)

RFC 1253 (OSPF v2)

RFC 1583 (OSPF v2)

RFC 1587 (OSPF NSSA Option)

RFC 1724 (RIP v2 MIB Extension)

RFC 1757 (RMON)

RFC 1812 (Requirements for IPv4 Routers)

RFC 1850 (OSPF v2)

RFC 1901 (Community Based SNMP v2)

RFC 1902 (SMI for SNMP v2)

RFC 1903 (SNMP v2 Text Conventions)

RFC 1904 (SNMP v2 Conformance)

RFC 1905 (SNMP v2 Protocol Operations)

RFC 1906 (SNMP v2 Transport Mappings)

RFC 1907 (SNMP v2c)

RFC 1908 (SNMP v1/2 Coexistence)

RFC 2021 (RMON II Probe Config)

RFC 2154 (OSPF Digital Signatures)

RFC 2233 (Interfaces)

RFC 2236 (IGMP v2)

RFC 2328 (OSPF v2)

RFC 2338 (VRRP)

RFC 2362 (PIM-SM)

RFC 2570 (SNMP v3 Framework)

RFC 2571 (FrameWork)

RFC 2571-2575 (SNMP)

RFC 2576 (SNMP v1/2/3 Coexistence)

RFC 2578 (SMI v2 Structure)

RFC 2579 (SMI v2 Text Conventions)

RFC 2580 (SMI v2 Conformance)

RFC 2613 (Remote Network Monitoring MIB Extensions)

RFC 2618 (RADIUS Authentication Client)

RFC 2620 (RADIUS Accounting Client)

RFC 2644 (Restricted Directed Broadcast)

RFC 2665 (Pause Control)

RFC 2674 (VLAN MIB Extension)

RFC 2819 (RMON groups Alarm, Event, History and Statistics only)

RFC 2819 (RMON)

RFC 3410 (Management Framework)

RFC 3414 (SNMP v3 USM)

RFC 3415 (SNMP v3 VACM)

RFC 3416 (SNMP Protocol Operations v2)

RFC 3417 (SNMP Transport Mappings)

SNMP v3 and RMON RFC support

EMISSIONS / AGENCY APPROVALS

CISPR 22 Class A

FCC Part 15 Class A

EN 55022 1998 Class A

EN 61000-3-2 2000, 61000-3-3

ICES-003 Class A

VCCI Class A

IMMUNITY

EN 55024

SAFETY AGENCY CERTIFICATIONS

UL 60950

IEC 60950-1

EN 60950-1

CAN/CSA-C22.2 No. 60950-1-03

WARRANTY AND OTHER SERVICES

Limited Lifetime Hardware Warranty, including fans and power supply

Limited Software Warranty for 90 days

Advance Hardware Replacement with Next Business Day shipment in most regions

Limited Lifetime software updates

90 days of telephone technical support

Refer to www.3com.com/warranty for details.

REDUNDANT POWER SYSTEM

3Com has tested and qualified a Redundant Power System (RPS) solution designed for the Switch 5500 family by Eaton Powerware Corporation, a leading global provider of power quality and management solutions.

The Powerware DC RPS systems come in either 3RU or 6RU form-factors, delivering up to 9,000W of DC power to a stack of Switch 5500 units.

The 3RU RPS unit houses up to three hot-swappable rectifiers supplying up to 4,500W of power that supports up to eight separately-fused DC outputs, while the 6RU unit can house up to six hot-swappable rectifiers provisioning a total of 9,000W.

The RPS supports SNMP management, including MIB II, which is easily accessible through the built-in RJ-45 or serial port. It is fully compatible with the IEEE 802.3af Power over Ethernet standard, providing supplemental power for the 3Com Switch 5500 PWR models.

With this RPS, all 384 10/100 ports on a stack of eight Switch 5500 PWR 52-port units can receive the industry standard 15.4W of power per port, with N+1 power redundancy.

The RPS ships with the power input fully configured and can be connected to a UPS with battery backup. For more details, refer to www.3com.com/rps.

ORDERING INFORMATION

PRODUCT DESCRIPTION	3COM SKU
3Com Switch 5500-EI 28-Port	3CR17161-91
3Com Switch 5500-EI 52-Port	3CR17162-91
3Com Switch 5500-EI PWR 28-Port	3CR17171-91
3Com Switch 5500-EI PWR 52-Port	3CR17172-91
3Com Switch 5500-EI 28-Port FX	3CR17181-91

Gigabit SFP Transceivers

3Com 1000BASE-SX SFP	3CSFP91
3Com 1000BASE-LX SFP	3CSFP92
3Com 1000BASE-T SFP	3CSFP93
3Com 1000BASE-LH SFP	3CSFP97

Fast Ethernet SFP Transceivers

3Com 100BASE-FX SFP [†]	3CSFP81
3Com 100BASE-LX10 SFP [†]	3CSFP82
3Com 100BASE-BX10-D SFP [†]	3CSFP85
3Com 100BASE-BX10-U SFP [†]	3CSFP86

3Com Global Services

3Com Network Health Check, Installation Services, and Express Maintenance	www.3com.com/services_quote
3Com University Courses	www.3com.com/3comu

[†] Only for use with Switch 5500-EI 28-Port FX, 3CR17181-91.

Visit www.3com.com for more information about 3Com secure converged network solutions.

3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064
3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2008 3Com Corporation. All rights reserved. 3Com, the 3Com logo, and XRN are registered trademarks, TippingPoint and VCX are trademarks, and Guardian and Express are service marks, of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. All specifications are subject to change without notice.

400907-021 04/08

