


Synergy 21 LED subordinate controller 1-channel amplifier Box IP66 *Milight/Miboxer*



Experience a new dimension of performance enhancement with the **1-Channel Amplifier Box**. The Amplifier Box has been specially developed for demanding applications and offers an **input voltage of AC100~240V** at a frequency of **50/60Hz**.

This powerful amplifier delivers an **output voltage of DC24V** and can achieve an impressive **output current of up to 8.5A**. With a maximum **output power of 200W**, the **1-Channel Amplifier Box** guarantees efficient amplification and reliable performance for your lighting systems.


The **IP66 protection class** ensures that the box is protected against dust and water, which increases its durability and reliability in various environments. Ideal for use in demanding or outdoor applications, the **SYS-PT2** offers a robust solution for your amplification needs. Optimise your systems with this high-quality **amplifier box** and benefit from stable and powerful signal amplification.

Product Name: 1-Channel Amplifier Box
Model No.: SYS-PT2
Input: AC100~240V 50/60Hz
Output Voltage: DC24V
Output Current: Max 8.5A
Output Power: Max 200W
IP Rate: IP66

Attributes

Attribute	Value
Ampere:	8.50
CC oder CV:	CV
Grösse:	263*184*81
Schutzklasse:	IP66
Volt:	24
Weight:	3 Kg
Warranty:	24.00 Months

Additional Images



Working on the amplifying the power and signal of "1-Channel Host Control Box"

Amplify the power and signal of 1-Channel Host Control Box;
When adding one more Amplifier Box, you can connect and control double lamps



Outdoor Using and Waterproof Waterproof rate is IP66'

Working normally at outdoor using in raining days



High quality stainless steel

Sun protection, corrosion resistance,
wind and rain protection, Fast heat dissipation



