


WIRING TYPE B Cross

1	Blue
2	Orange
3	Green
4	Brown
5	Gray
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Pink
12	Aqua



ITEM NO.	Length
S216785	0.5M
S216786	1M
S216787	2M
S216788	3M
S216789	5M
S216790	7.5M
S216791	10M
S216792	15M

Fiber Transfer Distance

	Wavelength	50/125 OM4
1 Gigabit Ethernet	850nm	1100m
10 Gigabit Ethernet	850nm	550m
40 Gigabit Ethernet	850nm	150m
100 Gigabit Ethernet	850nm	125m

MATERIAL LIST:

⑥	FIBER OPTICAL CABLE 12C OM4 50/125 Round Jacket LSZH Erika violet OD: 3.0mm	L	
⑤	MTP® Black Boot	2	
④	Housing Erika violet USconec	2	
③	Plastic Body Black USconec	2	
②	Resin Ferrule PC MM USconec MTP® ELITE	2	
①	MTP® Black Dust cover	2	

NO	SPECIFICATION STANDARD	QT'Y	REMARK
----	------------------------	------	--------

Note:

- RoHS 2011/65/EU and amendment directives (EU) 2015/863 compliant;REACH 1907/2006/EC compliant.
- Operating Temperature:0° C ~+60° C
- Storage Temperature:-20° C ~+70° C
- Min. bending radius : 10*D(Static) 20*D(Dynamic)
D:diameter of cable

Type	Multi-Mode
	MTP® ELITE LOW INSERTION LOSS
Insertion Loss	≤ 0.35dB (IEC 61300-3-4)
Return Loss	≥ 30dB (IEC 61300-3-6)
Test Wavelength	850nm

SinglePack: 1pc/SYNERGY21 A bag/test report+label;
SubPack: no; Carton +labelx2;

						SYNERGY 21				
						CUSTOMER			ITEM NO.	see the chart
Tan	Fan	Add the table about Transmission distance ⚠			2024-12-11	A1	PRODUCT NAME	MTP® ELITE F/F 12 Core OM4 Patch Cord	manufacture country:	CHINA UNIT mm
		NEW			2021-08-23	A0	DRAWNBY	CHECKBY	APPOBY	DATE
BY	CHK	REVISION RECORD MODIFICATIONS			DATE	REV.	SYNERGY 21	SYNERGY 21	SYNERGY 21	2021-08-23