



Network

Dome

PNV-A6081R-E1T

PNV-A6081R-E2T

2MP Camera with built-in 1TB / 2TB Ruggedized SSD
& WAVE VMS server



Key Features

- Powerful hardware means SolidEDGE is capable of recording up to 5 additional cameras for a total recording solution of 6 cameras (32Mbps total recording throughput)
 - Embedded Solid State Drive (SSD) 1TB (PNV-A6081R-E1T) and 2TB (PNV-A6081R-E2T) with WAVE VMS pre-loaded
 - SSD status health management
 - Free Cloud video management with WAVE sync
 - Includes 1-channel WAVE VMS Professional camera license
 - Max. 2MP resolution, Up to 120fps
 - HYPERLINK "mailto:0.007Lux@F1.3" 0.007Lux@F1.3, 1/30sec. (Colour), 0Lux (B/W, IR LED on)
 - 4.38~9.33mm(2.13x) motorized varifocal lens with Simple focus for easy remote adjustments
 - WiseIR 40m (131.23ft)
 - Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine)
 - H.265, H.264, MJPEG, WiseStream II, WiseStream III (Using AI engine)
 - PoE+(IEEE802.3at type 2, Class4), 12VDC, Power redundancy failover
 - Hard-coated dome bubble/IP66, IP67, IP6K9K, IK10+, NEMA4X
 - TPM with FIPS 140-2 level2, Secure boot, Verify firmware forgery
- NOTE: SolidEDGE does not support AI and Video analytics including on any connected cameras**

PNV-A6081R-E2T

2MP Camera with built-in 2TB Rugged SSD



Specifications

Video	
Imaging Device	1/2" CMOS
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360
Max. Framerate	H.265/H.264: Max. 120fps/100fps/60fps/50fps/30fps/25fps(120Hz/100Hz/60Hz/50Hz/30Hz/25Hz) MJPEG: Max. 30fps
Min. Illumination	Color: 0.008Lux(F1.3, 1/30sec, 30IRE) BW: 0.0008Lux(F1.3, 1/30sec, 30IRE), 0Lux(IR LED on), 30/25fps Color: 0.016Lux(F1.3, 1/60sec, 30IRE) BW: 0.0016Lux(F1.3, 1/60sec, 30IRE), 0Lux(IR LED on), 60/50fps Color: 0.032Lux(F1.3, 1/120sec, 30IRE) BW: 0.0032Lux(F1.3, 1/120sec, 30IRE), 0Lux(IR LED on), 120/100fps
Video Out	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation
Lens	
Focal Length (Zoom Ratio)	4.38~9.33mm(2.13x) motorized varifocal
Max. Aperture Ratio	F1.3(Wide)~F2.15(Tele)
Angular Field of View	H: 104°(Wide)~44°(Tele) V: 55°(Wide)~24°(Tele) D: 124°(Wide)~51°(Tele)
Min. Object Distance	0.5m(1.64ft)
Focus Control	Simple focus
Lens Type	P-iris(IR corrected)
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0°~360° / -45°~85° / 0°~355°
Operational	
Camera Title	Displayed up to 85 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, WDR, SSSDR
Wide Dynamic Range	120dB
Digital Noise Reduction	WiseNR, SSNR V
Motion Detection	8ea, 8point Polygonal zones
Privacy Masking	6ea, Rectangular zones - Color: Gray/Black/White
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC	Support

Electronic Shutter Speed	Minimum / Maximum / Prefer / Anti flicker(1/5~1/12,000sec)
Video Rotation	Flip, Mirror, Hallway view(90°/270°)
Analytics	SolidEDGE does not support AI and Video analytics including on any connected cameras
Alarm I/O	Input 1ea / Output 1ea
Alarm Triggers	Network disconnect, Alarm input, App event, Time schedule, MQTT subscription
Alarm Events	When alarm trigger occurred - File upload(image): e-mail/FTP - Notification: e-mail - Alarm output - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - Audio clip playback - MQTT: publication
Audio In	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
Audio Out	Line out, Max.output level: 1Vrms
IR Viewable Length	WiseIR 40m(131.23ft)

Network	
Ethernet	Metal shielded RJ-45(10/100/1000BASE-T)
Video Compression	H.265/H.264: Main/High, MJPEG
Audio Compression	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
Smart Codec	Manual(5ea area), WiseStream
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(6 users) / Multicast Multiple streaming(Up to 5 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), MQTT
Security	TPM 2.0(FIPS 140-2 level 2) HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Device Certificate(Hanwha Vision Root CA, pre-installed) Secure Boot, Verify firmware forgery
Application Programming Interface	ONVIF Profile S/T/M SUNAPI(HTTP API)

General	
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Greek, Hungarian

PNV-A6081R-E1T / PNV-A6081R-E2T

Edge Storage 1TB (PNV-A6081R-E1T) / 2TB (PNV-A6081R-E2T) SSD included(WAVE pre-installed)
Possible to register the maximum number of camera - up to 6 camera(Host + 5 camera)
- Total bandwidth: up to 33Mbps

***SolidEDGE does not support AI and Video analytics including on any connected cameras**

Memory 4GB RAM, 512MB Flash

Environmental & Electrical

Operating Temperature / Humidity -30°C~+55°C(-22°F~+131°F) / 0~95%RH(non-condensing)
* Start up should be done at above -20°C
Humidity control /w AIR vent

Storage Temperature / Humidity -50°C~+60°C(-58°F~+140°F) / 0~90% RH

Certification IP66/IP67/IP6K9K, NEMA4X, IK10

Input Voltage PoE+(IEEE802.3at type 2, Class4), 12VDC

Power Consumption PoE+: Max 19.2W, typical 14.4W
12VDC: Max 17.5W, typical 12.7W
Power redundancy failover

Mechanical

Color / Material White / Aluminum
Hard-coated dome bubble

RAL Code RAL9003

Product Dimensions / Weight ø180x130mm(ø7.09x5.12"), 1900g(4.19 lb)

Compatible Conduit hole / Gangbox 19.1mm(3/4")(M25)
single, double, 4" octagon, 4" square

Hanging Mount (Dome) SBP-187HMW

Certifications & Standards

EMC FCC 47 CFR 15 Subpart B Class A
ICES-3(A)/NMB-3(A)
CE/UKCA
- EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3
VCCI CISPR 32 Class A
RCM AS/NZS CISPR 32 Class A
KS C 9832 Class A, KS C 9835

Safety UL 62368-1, CAN/CSA C22.2 NO. 62368-1
IEC/EN 62471

Environment IEC/EN 63000
IEC/EN 60529 IP66/IP67, ISO 20653 IP6K9K, IEC/EN 62262 IK10
NEMA 250 type 4X

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF) Wide: 30.0m(98.43ft) / Tele: 95.0m(311.82ft)

Observe (63PPM/ 19PPF) Wide: 12.0m(39.37ft) / Tele: 38.0m(124.73ft)

Recognize (125PPM/ 38PPF) Wide: 6.0m(19.69ft) / Tele: 19.0m(62.36ft)

Identify (250PPM/ 76PPF) Wide: 3.0m(9.84ft) / Tele: 9.5m(31.18ft)