

Overview

Models

| | |
|--|--------|
| HP ProCurve 10-GbE SFP+ 1m Direct Attach Cable | J9281B |
| HP ProCurve 10-GbE SFP+ 3m Direct Attach Cable | J9283B |
| HP ProCurve 10-GbE SFP+ 7m Direct Attach Cable | J9285B |

Key Features

- SFF-8431 compliant
 - Supports 10-GbE data rate operation
 - Serial data transmission
-

Features and benefits

Warranty and support

- **ProCurve Lifetime Warranty:** for as long as you own the product, with next-business-day advance replacement (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to the HP Web site at www.procurve.com/support for details on the support provided and the period during which support is available

Technical Specifications

HP ProCurve 10-GbE
SFP+ 1m Direct Attach
Cable (J9281B)

Notes

Electrical Properties

- Cable Characteristic Impedance: 100 ohms
- Crosstalk between pairs: 2% max
- Time delay: 1.31 nsec/ft

Physical Properties

- Cable Diameter: 0.180"
- Minimum Cable Bend Radius: 1.0"
- Temperature Range: 0°–65°C

Services

Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP ProCurve 10-GbE
SFP+ 3m Direct Attach
Cable (J9283B)

Notes

Electrical Properties

- Cable Characteristic Impedance: 100 ohms
- Crosstalk between pairs: 2% max
- Time delay: 1.31 nsec/ft

Physical Properties

- Cable Diameter: 0.180"
- Minimum Cable Bend Radius: 1.0"
- Temperature Range: 0° – 65°C

Services

Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP ProCurve 10-GbE
SFP+ 7m Direct Attach
Cable (J9285B)

Notes

Electrical Properties

- Cable Characteristic Impedance: 100 ohms
- Crosstalk between pairs: 2% max
- Time delay: 1.31 nsec/ft

Physical Properties

- Cable Diameter: 0.180"
- Minimum Cable Bend Radius: 1.0"
- Temperature Range: 0° – 65°C

Services

Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

To learn more, visit www.hp.com/go/procurve

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.